

Fixing Matrix - Wall Framing 1 of 2

Wall Framing Product											
Plate to Stud Plates up to 38mm thick (Through plate nailing)									●	●	●
Plate to Stud Plates up to 50mm thick (Through plate nailing)											
Plate to Stud Plates up to 50mm thick (Skew nailed through stud)									●	●	●
Nogging to Stud									●	●	●
Timber braces to Stud or Plate	●	●	●	●	●	●	●	●			
Lintel to Jamb Stud	●	●	●	●	●	●	●	●			
Bottom Plate to Joist Plates up to 38mm thick (At max. 600mm spacings)									●	●	●
Bottom Plate to Joist Plates up to 50mm thick (At max. 600mm spacings)											
All above recommendations require two (2) nail fixings at each connection point											
Multiple Studs (Single nail at max. 600mm spacings)									●	●	●
Impulse Framing Nailers											
Paslode Impulse FrameMaster-Li B20543P								●	●		
Paslode Impulse IM90Ci B30190											
Pneumatic Framing Nailers											
Paslode Pneumatic PowerMaster PF350S B20430				●	●				●	●	●
Pneumatic Coil Nailers											
Paslode Pneumatic Coil Nailer CNW 57 B21094				●							
Paslode Pneumatic Coil Nailer CNW 70 B21095				●							
Duo-Fast Pneumatic Coil Nailer CNP-50 D40010	●	●									
Duo-Fast Pneumatic Coil Nailer CNP-65 D40030	●	●									
	Duo-Fast Pneumatic Coil 50 x 2.5mm Bright D41350	Duo-Fast Pneumatic Coil 50 x 2.5mm HD Galvanised Ring D41510	Paslode Pneumatic Coil 50 x 2.5mm HD Galvanised Ring B26265 or B25140	Paslode Pneumatic JDN 50 x 2.87mm Bright D Head B20463	Paslode Pneumatic JDN 50 x 2.87mm HD Galvanised D Head B20528D	Paslode Pneumatic JDN 50 x 2.87mm Bright D Head Value Pack B20544V	Paslode Impulse 50 x 2.87mm HD Galvanised D Head B20552 or B20565V	Paslode Pneumatic JDN 75 x 3.06mm Bright D Head B20467	Paslode Pneumatic JDN 75 x 3.06mm HD Galvanised D Head B20529D	Paslode Pneumatic JDN 75 x 3.06mm Bright Ring D Head B20539	

Fixing Matrix - Wall Framing 2 of 2

Wall Framing Product									
Plate to Stud Plates up to 38mm thick (Through plate nailing)	●	●	●	●	●				
Plate to Stud Plates up to 50mm thick (Through plate nailing)						●	●	●	●
Plate to Stud Plates up to 50mm thick (Skew nailed through stud)	●	●	●	●	●				
Nogging to Stud	●	●	●	●	●				
Timber braces to Stud or Plate									
Lintel to Jamb Stud									
Bottom Plate to Joist Plates up to 38mm thick (At max. 600mm spacings)	●	●	●	●	●				
Bottom Plate to Joist Plates up to 50mm thick (At max. 600mm spacings)						●	●	●	●
All above recommendations require two (2) nail fixings at each connection point									
Multiple Studs (Single nail at max. 600mm spacings)	●	●	●	●	●				
Impulse Framing Nailers									
Paslode Impulse FrameMaster-Li B20543P	●	●	●					●	●
Paslode Impulse IM90Ci B30190				●	●				
Pneumatic Framing Nailers									
Paslode Pneumatic PowerMaster PF350S B20430						●	●		
Pneumatic Coil Nailers									
Paslode Pneumatic Coil Nailer CNW 57 B21094									
Paslode Pneumatic Coil Nailer CNW 70 B21095									
Duo-Fast Pneumatic Coil Nailer CNP-50 D40010									
Duo-Fast Pneumatic Coil Nailer CNP-65 D40030									
	Paslode Impulse 75 x 3.06mm Bright D Head B20551 or B20547V	Paslode Impulse 75 x 3.06mm HD Galvanised D Head B20554 / B20569V	Paslode Impulse 75 x 3.06mm Bright Ring D Head B20563V	Paslode Impulse IM90Ci 75 x 3.06mm Bright R Drive B31200T	Paslode Impulse IM90Ci 75 x 3.06mm HD Galvanised R Drive B31250T	Paslode Pneumatic JDN 90 x 3.15mm Bright D Head B20469	Paslode Pneumatic JDN 90 x 3.15mm HD Galvanised D Head B20529F	Paslode Impulse 90 x 3.15mm Bright D Head B20550 or B20550V	Paslode Impulse 90 x 3.15mm HD Galvanised D Head B20571 or B20571V